



Main

| | |
|-----------------------------|------------------------|
| Range | Actassi |
| Product brand | Schneider Electric |
| Product type | Keystone modular jack |
| Provided equipment | Without shutter |
| Colour tint | White |
| Wiring colour configuration | TIA-568A/B |
| Type of packing | Plastic bag and carton |
| Quantity per set | Set of 1 |

Complementary

| | |
|--------------------------------|---|
| [In] rated current | 1.5 A at 25 °C |
| Voltage proof | 1000 V AC/DC peak, between contacts |
| Contact resistance | 20 mOhm |
| Insulation resistance | >= 500 mOhm |
| AWG gauge | AWG 24...AWG 22 |
| Mechanical durability | 750 cycles |
| Tool type | Punch down tool Quick termination tool |
| Cable outer diameter | 0.9...1.4 mm |
| Compatible LAN cable types | UTP |
| Communication network category | 5e |
| Supported applications | 1000BASE-T |
| Protocols | PoE+ (Power over Ethernet) |
| Product compatibility | RJ45 plug RJ11 plug |
| Type of footprint | S-110 keystone |
| Targeted region | Asia Pacific |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

| | |
|-------------------------------------|---|
| Operational temperature range | -10...60 °C |
| Ambient air temperature for storage | -20...70 °C |
| Climatic category | 40/070/21 21 days |
| Flame retardance | UL94-V0 conforming to UL listed |
| Environmental characteristic | RoHS compliant REACH |
| Product certifications | FCC part 68 F IEC 60603-7 |
| Standards | IEC 11801 class E NZS 3080:2003 class E TIA/EIA 568 B |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product Environmental Profile |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|