



Main

Range	Actassi
Product brand	Schneider Electric
Product type	30Mech modular jack
Provided equipment	With shutter
Colour tint	White
Wiring colour configuration	TIA-568A/B
Type of packing	Plastic bag and carton
Quantity per set	Set of 1

Complementary

[In] rated current	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts
Contact resistance	20 mOhm
Insulation resistance	>= 500 mOhm
Connector type	RJ45
AWG gauge	AWG 24...AWG 23
Tool type	Punch down tool Quick termination tool
Cable outer diameter	0.7...1.4 mm
Compatible LAN cable types	UTP
Communication network category	6
Supported applications	1000BASE-T
Product compatibility	RJ45 plug RJ11 plug
Type of footprint	S-110 30 mech
Targeted region	Asia Pacific

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Operational temperature range	-10...60 °C
Ambient air temperature for storage	-20...70 °C
Climatic category	40/070/21 21 days
Flame retardance	UL94-V0 conforming to UL listed
Environmental characteristic	RoHS compliant REACH
Product certifications	FCC part 68 F IEC 60603-7
Standards	IEC 11801 class E TIA/EIA 568 B NZS 3080:2003

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1636 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------