



Main

Range	Digilink
Product name	Digilink G600
Product or component type	Copper cable
Device application	Transmission
Cable shielding type	S/FTP
Communication network category	6
Colour tint	Grey

Complementary

Type of cable	4 twisted pair cables
Conductor material	Copper
Input impedance	100 Ohm (+/- 6) at 1...300 MHz
DC resistance	72 Ohm per 1 km
[Ue] rated operational voltage	72 V DC (maximum)
Dielectric strength	1500 V for 1 min at 1 MHz
Insulation resistance	>= 500 MOhm/km500 V DC
Nominal velocity propagation	69 %
Cable outer diameter	7.3 mm
Cable length	305 m
AWG gauge	AWG 23
Material	PVC (polyvinyl chloride): jacket Tinned copper: shield

Environment

Product certifications	UL listed ETL verified
Standards	ANSI/TIA/EIA-568-C.2

Packing Units

Package 1 Weight	23.000 kg
Package 1 Height	2.500 cm
Package 1 width	4.000 cm
Package 1 Length	4.000 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile