



## Main

Range	Actassi
Product brand	Schneider Electric
Product type	Keystone modular jack
Product specific application	For panel
Provided equipment	Without shutter
Colour tint	Metal (zamak)
Wiring colour configuration	TIA-568A/B
Type of packing	Plastic bag and carton
Quantity per set	Set of 1


## Complementary

[In] rated current	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts
Contact resistance	20 mOhm
Insulation resistance	>= 500 mOhm
Connector type	RJ45
Tool type	Punch down tool Quick termination tool
Cable outer diameter	0.9...1.4 mm
Compatible LAN cable types	FTP
Communication network category	6A
Supported applications	10GBASE-T
Product compatibility	RJ45 plug RJ11 plug
Type of footprint	S-110 keystone
Targeted region	Asia Pacific

## Environment

Operational temperature range	-10...60 °C
Ambient air temperature for storage	-20...70 °C
Relative humidity	0...93 %
Climatic category	40/070/21 21 days
Flame retardance	UL94-V0 conforming to UL listed
Environmental characteristic	RoHS compliant REACH
Product certifications	FCC part 68 F IEC 60603-7
Standards	IEC 60603-7 ANSI/TIA/EIA-568-B ISO/IEC 11081

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity <a href="#"> Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------