



### Main

Range	Actassi
Product	Patch cord
Colour	Blue
Cable shielding type	UTP

### Complementary

Performance	4 pair cables
Rated voltage	150 V AC
[In] rated current	1.5 A
Insulation resistance	1 MOhm
Cable length (customisable value in configurator)	0...5 m
Communication network category	5e
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Contact resistance	10 mOhm
AWG	AWG 24
Return loss	Guaranteed: $\geq 20$ dB
Number of matings	$\geq 1000$ cycles
Targeted region	Asia Pacific

### Environment

Flame retardance	CM
Standards	IEC 60603-7 AS/NZS 3080:2003 FCC part 68 subpart F

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

---

REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available  <a href="#">Product Environmental Profile</a>
Product end of life instructions	Need no specific recycling operations

---

### [Contractual warranty](#)

---

Warranty period	18 months
-----------------	-----------

---