



Main

Range	Actassi
Product	Patch cord
Colour	Blue
Cable shielding type	UTP

Complementary

Performance	4 pair cables
Rated voltage	150 V AC
[In] rated current	1.5 A
Insulation resistance	500 MOhm
Cable length (customisable value in configurator)	0...3 m
Communication network category	6
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Contact resistance	10 mOhm
AWG	AWG 24
Return loss	Guaranteed: ≥ 27 dB
Attenuation	Guaranteed: 0.1 dB
Far end crosstalk [FEXT]	49.8 dB
Near end crosstalk [NEXT]	Guaranteed: 55.1 dB
Power sum far end crosstalk [PSFEXT]	46.9 dB
Power sum near-end crosstalk [PS NEXT]	Guaranteed: 52 dB
Number of matings	≥ 1000 cycles
Targeted region	Asia Pacific

Environment

Flame retardance	CM
------------------	----

Standards	IEC 60603-7 ISO/IEC 11801 2nd edition AS/NZS 3080:2003 TIA/EIA-568-B FCC part 68 subpart F
-----------	--

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product Environmental Profile
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------