



### Main

Range	Actassi
Product	Patch cord
Colour	Blue
Cable shielding type	UTP

### Complementary

Performance	4 pair cables
Rated voltage	150 V AC
[In] rated current	1.5 A
Insulation resistance	500 MOhm
Cable length (customisable value in configurator)	0...2 m
Communication network category	6
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Contact resistance	10 mOhm
AWG	AWG 24
Return loss	Guaranteed: $\geq 27$ dB
Attenuation	Guaranteed: 0.1 dB
Far end crosstalk [FEXT]	49.8 dB
Near end crosstalk [NEXT]	Guaranteed: 55.1 dB
Power sum far end crosstalk [PSFEXT]	46.9 dB
Power sum near-end crosstalk [PS NEXT]	Guaranteed: 52 dB
Number of matings	$\geq 1000$ cycles
Targeted region	Asia Pacific

### Environment

Flame retardance	CM
------------------	----

Standards	IEC 60603-7 ISO/IEC 11801 2nd edition AS/NZS 3080:2003 TIA/EIA-568-B FCC part 68 subpart F
-----------	--------------------------------------------------------------------------------------------------------

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product Environmental Profile</a>
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------