



Main

Range	Actassi
Product	Patch cord
Colour	Blue
Cable shielding type	FTP

Complementary

Performance	4 pair cables
Rated voltage	150 V AC
[In] rated current	1.5 A
Insulation resistance	500 MOhm
Cable length (customisable value in configurator)	0...1 m
Communication network category	6
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Contact resistance	10 mOhm
AWG	AWG 26
Return loss	Guaranteed: ≥ 27 dB
Attenuation	Guaranteed: 0.1 dB
Far end crosstalk [FEXT]	49.8 dB
Near end crosstalk [NEXT]	Guaranteed: 55.1 dB
Power sum far end crosstalk [PSFEXT]	46.9 dB
Power sum near-end crosstalk [PS NEXT]	Guaranteed: 52 dB
Number of matings	≥ 1000 cycles
Targeted region	Asia Pacific

Environment

Flame retardance	CM
Standards	IEC 60603-7 ISO/IEC 11801 2nd edition AS/NZS 3080:2003 TIA/EIA-568-B

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------