



Main

Range	Actassi
Product	Patch cord
Colour	Grey : patchcord
Quantity per set	1
Cable shielding type	S/FTP
Provided component	Grey coloured clips Green coloured clips Red coloured clips

Complementary

Product compatibility	Coloured clips yellow Coloured clips blue Coloured clips red Coloured clips green
Cable length (customisable value in configurator)	0...10 m
Communication network type	10GBASE-T
Connector type	RJ45
Communication network category	6A
Transmission frequency	550 MHz
AWG	AWG 26
Input impedance	100 Ohm
Material	Solid bare copper : conductor PE (polyethylene) : wire insulation
Targeted region	Europe

Environment

Ambient air temperature for installation	0...50 °C
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-20...60 °C
Temperature resistance	60 °C
Product certifications	Delta
Standards	ISO/IEC 11801:2011 Ed.2.2

Environmental characteristic	LSZH (low smoke zero halogen) jacket
------------------------------	--------------------------------------

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1144 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
------------------------	---

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
-------	--

Product end of life instructions	Need no specific recycling operations
----------------------------------	---------------------------------------

Contractual warranty

Warranty period	18 months
-----------------	-----------
